



XCE 1422 N4 COVER

- NOTES:
- 1. MINIMUM SPACING FROM CENTER OF OPERATOR TO NEAREST FLAT IS 1 1/2.
 - 2. MINIMUM SPACING BETWEEN 1-14 NPSM OPERATOR CENTERS IS 3 FOR THIS ENCLOSURE.
 - 3. MAXIMUM NUMBER OF OPERATORS IS 24.
 - 4. DIMENSION FROM CENTER LINES OF COVER FOR OPERATORS.
 - 5. DIMENSION FROM CENTER LINE AND BACK OF MTG. LUG FOR CONDUIT.
 - 6. FOR MTG. ENCLOSURE USE 1/2 BOLT.

COVER DRILLING ALLOWABLE IN XCE ONLY

<small>DO NOT SCALE DRAWING</small> <small>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES.</small> <small>CAST TOLERANCES ON DIMENSIONS NOT OTHERWISE SPECIFIED:</small> <small>1/2" = 1/16" STOCK</small> <small>FILLET OR CORNER RADII 1/8"</small> <small>CHAMF 1/16"</small> <small>FRAC ± 1/16"</small> <small>ANGLES ± 1°</small> <small>MACHINE TOLERANCES ON DIMENSIONS NOT OTHERWISE SPECIFIED:</small> <small>1/2" = 1/32"</small> <small>1/4" = 1/64"</small> <small>3/16" = 1/32"</small> <small>1/8" = 1/64"</small> <small>EDGE BREAK .005" - .015" R. or 45°</small> <small>ANGLES ± 0-30°</small> <small>GAGING FOR THERMAD HOLE</small> <small>NOT OTHERWISE SPECIFIED:</small> <small>NPSM E-24-1.0</small>		ADALET <small>A SCOTT FETZER COMPANY</small> <small>Enclosure Systems • Cable Accessories</small>		<small>NOTICE TO PERSONS RECEIVING THIS DRAWING:</small> <small>ADALET-PLM CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL DISCLOSED HEREIN. THIS DRAWING IS ISSUED IN CONFIDENCE FOR EXHAUSTIVE INFORMATION ONLY AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWING HEREIN WITHOUT EXPRESS WRITTEN PERMISSION FROM ADALET-PLM TO THE USER.</small> <small>MATERIAL:</small> SEE NOTES		<small>TITLE</small> MODIFIED XCE 142210 N4 ENCLOSURE FOR	
<small>DRAWN BY</small> AAM		<small>DATE</small> 11/12/02		<small>DRWG APPROVAL</small> <small>PLAY SCALE</small> 1=3.5		<small>MFG APPROVAL</small> <small>DRWG REE</small> D	
<small>FINISH</small> TUMBLAST		<small>DWG NO</small>		<small>SET</small> 10F1		<small>REV</small>	
<small>CAT NO</small> XCE 142210 N4							