



### XCE 1624 COVER

NOTES:

- COVER DRILLING ALLOWABLE IN XCE ONLY
1. MINIMUM SPACING FROM CENTER OF OPERATOR TO NEAREST FLAT IS 1 1/8.
  2. MINIMUM SPACING BETWEEN 3/4-14 NPSM OPERATOR CENTERS IS 3 1/2 FOR THIS ENCLOSURE.
  3. MAXIMUM NUMBER OF OPERATORS IS 24.
  4. DIMENSION FROM CENTER LINES OF COVER FOR OPERATORS.
  5. DIMENSION FROM CENTER LINE AND BACK OF MTG. LUG FOR CONDUIT.
  6. FOR MTG. ENCLOSURE USE 5/8 BOLT.

<small>DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. CAST TOLERANCES ON DIMENSIONS NOT OTHERWISE SPECIFIED: 1/2" = 1/16" STOCK FILLET OR CORNER RADII 1/8" DIA. ± 1/32" FRAC. ± 1/16" ANGLES ± 1° MACHINE TOLERANCES ON DIMENSIONS NOT OTHERWISE SPECIFIED: 1/4" = 1/32" 1/8" = .015" 1/16" = .010" EDGE BREAK .005"-.015" R. or 45° ANGLES ± 0°-30° GAGING FOR THERMAD HOLE NOT OTHERWISE SPECIFIED: NPSM E-21-2.6 NPSM E-24-1.6</small>	<b>ADALET</b> A SCOTT FETZER COMPANY Enclosure Systems • Cable Accessories	TITLE: MODIFIED XCE/XJF 162410 ENCLOSURE FOR	
		DRAWN BY: DDH	DATE: 11-15-01
		ENG APPROVAL:	PLOT SCALE: 1=4.5
		MFG APPROVAL:	DWG CODE: D
FINISH: TUMBLAST	CAT NO: XCE/XJF 162410	DWG NO:	SET: 10F1