



XCE 0812 COVER

- NOTES:
1. MINIMUM SPACING FROM CENTER OF OPERATOR TO NEAREST FLAT IS 1 1/8.
 2. MINIMUM SPACING BETWEEN 3-14 NPSM OPERATOR CENTERS IS 2 1/2 FOR THIS ENCLOSURE.
 3. MAXIMUM NUMBER OF OPERATORS IS 8.
 4. DIMENSION FROM CENTER LINES OF COVER FOR OPERATORS.
 5. DIMENSION FROM CENTER LINE AND BACK OF MTG. LUG FOR CONDUIT.
 6. FOR MTG. ENCLOSURE USE 3/8 BOLT.

<small>DO NOT SCALE DRAWING</small> <small>UNLESS OTHERWISE SPECIFIED</small> <small>DIMENSIONS ARE IN INCHES</small> <small>CAST TOLERANCES ON DIMENSIONS</small> <small>NOT OTHERWISE SPECIFIED:</small> <small>1/2" = 1/8" STOCK</small> <small>FLAT OR CORNER RADII 1/8"</small> <small>HOLES 1/16"</small> <small>FRAC ± 1/16"</small> <small>ANGLES ± 1°</small> <small>MACHINE TOLERANCES ON DIMENSIONS</small> <small>NOT OTHERWISE SPECIFIED:</small> <small>1/4" = 1/32"</small> <small>1/8" = .015"</small> <small>1/16" = .010"</small> <small>EDGE BREAK .005" - .015" R. or 45°</small> <small>ANGLES ± 0-30°</small> <small>GAGING FOR THERMAD HOLE</small> <small>NOT OTHERWISE SPECIFIED:</small> <small>NPSM E-24-2.0</small> <small>NPSM E-24-1.0</small>	<p style="text-align: center;">ADALET</p> <p style="text-align: center;"><small>A SCOTT FETZER COMPANY</small></p> <p style="text-align: center;"><small>Enclosure Systems • Cable Accessories</small></p>	<small>TITLE</small> MODIFIED XCE/XJF 081208 ENCLOSURE FOR	
		<small>NOTICE TO PERSONS RECEIVING THIS DRAWING:</small> ADLET-PLM CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL RECLOSED HEREIN. THIS DRAWING IS ISSUED IN CONFIDENCE FOR EXHAUSTIVE INFORMATION ONLY AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN HEREIN WITHOUT WRITTEN PERMISSION FROM ADLET-PLM TO THE USER.	<small>DRAWN BY</small> DDH
<small>DATE</small> 1/01	<small>ENG APPROVAL</small> [Signature]	<small>PLAT SCALE</small> 1=2.5	<small>DWG NO</small> D
<small>PERISH</small> TUMBLAST	<small>DWG NO</small> XCE/XJF 081208	<small>REV</small> 10F1	<small>REV</small> [Blank]