REV	REVISION	BY	ECN	DATE













XCE 1224 COVER

COVER DRILLING ALLOWABLE IN XCE ONLY

NOTES:

1. MINIMUM SPACING FROM CENTER OF OPERATOR TO NEAREST FLAT IS $1\frac{1}{16}$.
2. MINIMUM SPACING BETWEEN $\frac{3}{4}$–14 NPSM OPERATOR CENTERS IS 3 FOR THIS ENCLOSURE.
3. MAXIMUM NUMBER OF OPERATORS IS 21.
4. DIMENSION FROM CENTER LINES OF COVER FOR OPERATORS.
5. DIMENSION FROM CENTER LINE AND BACK OF MTG. LUG FOR CONDUIT.
6. FOR MTG. ENCLOSURE USE $\frac{1}{2}$ BOLT.

DO NOT SCALE DRAWING
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES.
CAST TOLERANCES ON DIMENSIONS NOT OTHERWISE SPECIFIED:
4 = 1/8 STOCK
FILLET OR CORNER RADII 1/8"
DRAFT 1 1/2°
FRAC. ±1/16
ANGLES ± 1°
MACHINED TOLERANCES ON DIMENSIONS NOT OTHERWISE SPECIFIED:
4 = 125
XX ± .03" .XXX ± .010"
FILLET RADII .03"
EDGE BREAK .005"–.015" R. or 45° ANGLES ± 0°–30°
GAGING FOR THREADED HOLES NOT OTHERWISE SPECIFIED:
NPT E-21-2.8
NPSM E-24-1.0

ADALET
A SCOTT FETZER COMPANY
Enclosure Systems • Cable Accessories

NOTICE TO PERSONS RECEIVING THIS DRAWING:
ADALET-PLM CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL DISCLOSED HEREON. THIS DRAWING IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN HEREIN WITHOUT DIRECT WRITTEN PERMISSION FROM ADALET-PLM TO THE USER.

MATERIAL
FINISH TUMBLAST
CAT NO XCE/XJF 122406

TITLE
MODIFIED XCE/XJF 122406 ENCLOSURE FOR

DRAWN BY	DDH	DATE	11–12–01
ENG APPROVAL		PLOT SCALE	1=4
MFG APPROVAL		DWG SIZE	D
DWG NO		SHT	1OF1
		REV	