



XCE 1824 COVER

NOTES:

- COVER DRILLING ALLOWABLE IN XCE ONLY
- MINIMUM SPACING FROM CENTER OF OPERATOR TO NEAREST FLAT IS 1 1/8.
- MINIMUM SPACING BETWEEN 3/4"-14 NPSM OPERATOR CENTERS IS 3 1/2 FOR THIS ENCLOSURE.
- MAXIMUM NUMBER OF OPERATORS IS 24.
- DIMENSION FROM CENTER LINES OF COVER FOR OPERATORS.
- DIMENSION FROM CENTER LINE AND BACK OF MTC. LUG FOR CONDUIT.
- FOR MTC. ENCLOSURE USE 3/8" BOLT.

<small>DO NOT SCALE DRAWING</small> <small>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</small> <small>CAST TOLERANCES ON DIMENSIONS NOT OTHERWISE SPECIFIED: 1/2" = 1/16" STOCK</small> <small>1/2" = 1/32" STOCK</small> <small>FILLET OR CORNER RADII 1/8"</small> <small>SHAFT 1/2"</small> <small>FRAG ± 1/16"</small> <small>ANGLES ± 1°</small> <small>MACHINE TOLERANCES ON DIMENSIONS NOT OTHERWISE SPECIFIED: 1/2" = 1/32"</small> <small>1/2" = .03"</small> <small>1/2" = .03"</small> <small>EDGE BREAK .005" - .015" R. or 45°</small> <small>ANGLES ± 0-30°</small> <small>GAGING FOR THERMIST HOLES</small> <small>NOT OTHERWISE SPECIFIED: NPSM E-24-2.0</small> <small>NPSM E-24-1.0</small>		ADALET <small>A SCOTT FETZER COMPANY</small> <small>Enclosure Systems • Cable Accessories</small>		<small>NOTICE TO PERSONS RECEIVING THIS DRAWING: ADALET-PLM CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL ENCLOSED HEREIN. THIS DRAWING IS ISSUED IN CONFIDENCE FOR EXHAUSTIVE INFORMATION ONLY AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN HEREIN WITHOUT EXPRESS WRITTEN PERMISSION FROM ADALET-PLM TO THE USER.</small> <small>MATERIAL: TUMBLAST</small>		<small>MODIFIED XCE/XJF 182406 ENCLOSURE FOR</small>	
<small>SEE NOTES</small>		<small>DRAWN BY DDH</small>		<small>DATE 11-16-01</small>		<small>SCALE 1=5</small>	
<small>SEE NOTES</small>		<small>DWG APPROVAL</small>		<small>DWG NO. D</small>		<small>REV</small>	
<small>SEE NOTES</small>		<small>DWG NO. XCE/XJF 182406</small>		<small>SET</small>		<small>REV</small>	
<small>SEE NOTES</small>		<small>10F1</small>					