



XCE 1830 N4 COVER

NOTES:

- 1. MINIMUM SPACING FROM CENTER OF OPERATOR TO NEAREST FLAT IS $1\frac{1}{8}$.
- 2. MINIMUM SPACING BETWEEN $\frac{3}{4}$ -14 NPSM OPERATOR CENTERS IS $3\frac{1}{2}$ FOR THIS ENCLOSURE.
- 3. MAXIMUM NUMBER OF OPERATORS IS 32.
- 4. DIMENSION FROM CENTER LINES OF COVER FOR OPERATORS.
- 5. DIMENSION FROM CENTER LINE AND BACK OF MTG. LUG FOR CONDUIT.
- 6. FOR MTG. ENCLOSURE USE $\frac{5}{8}$ BOLT.

<small>DO NOT SCALE DRAWING</small> <small>UNLESS OTHERWISE SPECIFIED</small> <small>DIMENSIONS ARE IN INCHES.</small> <small>CAST TOLERANCES OR DIMENSIONS</small> <small>NOT OTHERWISE SPECIFIED:</small> <small>1/2" = 1/16" STOCK</small> <small>FLAT OR CORNER RADII 1/8"</small> <small>CHAMF 1/32"</small> <small>FINISH ± 1/16"</small> <small>ANGLES ± 1°</small> <small>MACHINE TOLERANCES ON DIMENSIONS</small> <small>SHOWN NOT OTHERWISE SPECIFIED:</small> <small>1/2" = 1/32"</small> <small>1/4" = .015"</small> <small>1/8" = .005"</small> <small>EDGE BREAK .005"-.015" R. or 45°</small> <small>ANGLES ± 0-30°</small> <small>GAGING FOR THERMAD HOLE</small> <small>NOT OTHERWISE SPECIFIED:</small> <small>NPSM E-21-1.0</small>	ADALET <small>A SCOTT FETZER COMPANY</small> <small>Enclosure Systems • Cable Accessories</small>	<small>TITLE</small> MODIFIED XCEQ 183008 N4 ENCLOSURE FOR	
		<small>NOTICE TO PERSONS RECEIVING THIS DRAWING:</small> <small>ADALET-PLM CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL</small> <small>DISCLOSED HEREIN. THIS DRAWING IS ISSUED IN CONFIDENCE</small> <small>FOR EXAMINATION PURPOSES ONLY AND MAY NOT BE REPRODUCED</small> <small>OR USED TO MANUFACTURE ANYTHING SHOWN HEREON WITHOUT</small> <small>EXPLICIT WRITTEN PERMISSION FROM ADALET-PLM TO THE USER.</small>	<small>DRAWN BY</small> DDH
<small>PERISH</small> TUMBLAST	<small>ENG APPROVAL</small> [Signature]	<small>PLANT SCALE</small> 1=4	<small>DWG NO.</small> D
<small>CAF NO</small> XCEQ 183008 N4	<small>DWG NO.</small> [Signature]	<small>SHEET</small> 10F1	<small>REV</small> [Signature]